APLITAPE 4075

HEAVYWEIGHT PAPER APPLICATION TAPE

TECH DATA SHEET

4075 is standard weight saturated paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics.

PHYSICAL SPECIFICATIONS

Adhesive	Rubber-based
Color	White/Translucent
Caliper facestock	100-113 microns (4..0 -4.5 mils)
Caliper facestock + adhesive	125-138 microns (5.0 - 5.5 mils)
Adhesion to Steel*	18 - 20 N/100mm (16 - 18 oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance	50
Shelf Life**	1 year

FEATURES

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

APPLICATIONS

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

RESPONSIVE
RELIABLE
RESOURCEFUL

MAN PRINT & SIGN B.V.
G.G. Schipperstraat 26
1483 GE, De Rijp
T: 0031-(0)299-393390
sales@manprint-sign.nl
www.manprint-sign.nl