POLI-TAPE®

TECHNICAL DATASHEET
ISSUE: 1
DATE: 02/06/2026

PT 133

PRODUCT INFORMATION

Application tape made from a special impregnated paper with low tensile elongation and high wet strength. Suitable for transferring self-adhesive lettering produced using the CAD/CAM process from cast and calendered PVC color films.

Especially to be emphasised are the following properties:

- The natural latex adhesive is specifically formulated for transferring PVC films and guarantees excellent adhesion due to a high adhesive application rate.
- The impregnated backing paper exhibits excellent flatness and dimensional stability when exposed to moisture.
- The tape's translucency facilitates the application of even small lettering and logos.

TECHNICAL DATA

Carrier: Impregnated paper
Adhesive: Natural rubber
Adhesion [N/cm]: 2,40 +/- 10 %
Thickness [mm]: 0,10 +/- 10 %

STANDARD DIMENSIONS

1.220 mm x 100 m
1.220 mm x 91,4 m
1.000 mm x 100 m
1.000 mm x 91,4 m

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoff V and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 (REACH) and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

DISCLAIMER

The information on the physical and chemical properties and values contained in this document is based on tests we believe to be reliable; however, it does not constitute a guarantee. It is provided for informational purposes only, without warranty, and does not establish any guarantee. Buyers should independently verify the suitability of this material for their specific intended use prior to use. All technical data is subject to change. All POLI-TAPE products are sold in accordance with the terms and conditions of sale. For further information, please contact your POLI-TAPE sales representative. In the event of any ambiguity or discrepancy between the English version and foreign-language versions of this document, the English version shall prevail and take precedence.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen - GERMANY
Phone: +49 2642 - 98 36 0
Fax: +49 2642 - 98 36 37
Email: info@poli-tape.de
Internet: www.poli-tape.de